Seal WP Spot Light




A fixed recess-mounted LED waterproof downlight with a deep anti-glare design, die-cast aluminum body, and efficient heat sink. Finished in sandy white powder coating, it features an anti-glare lens for comfortable, high-quality illumination.









General Information

Shape

Mounting Ceiling Recessed

Lighting Application General Outdoor, Bathrooms, Kitchens

D 87mm | 110mm | 130mm | 160mm | 190mm | 225mm Dimension H 58mm | 67mm | 75mm | 84mm | 98mm | 115mm

Housing Material Die-cast Aluminum

White/White | White/Black Housing Color

Ingress Protection IP65

Lamp Characteristics

Lamp Туре

Light Source

Efficacy

Luminous Flux

Color Temperature

Color Rendering Index

Beam Angle

Control Gear

LED

COB

1400lm | 1960lm | 2800lm | 4480lm | 6020lm | 8540lm

140 lm/W

3000K | 4000K | 5000K

>80 Ra

30° | 60°

On-Off

Electrical Information

Total Power 10W | 14W | 20W | 32W | 43W | 61W Voltage 220V AC

Product Code Not interselectable**

Brand (BR-)	Product (PRO)	Mounting (MO)	Dimension (DM)**	Body/Baffle Color (BB)	IP Rating (IP)	Lumen (LUM)**	CCT (CT)	Beam Angle (BA)	Control (C)	
Zarelux (ZL-)	Seal WP Spot Light (SWS)	Ceiling Recessed (CR)	D 87mm (87)	White/White	IP65 (65)	1400lm (140)	3000K (30)	30deg (30)	On-Off (O)	
	Light (SWS)	(City	D 110mm (11)	White/Black		1960lm (196)	4000K (40)	60deg (60)		
			D 130mm (13)	(****)		2800lm (280)	5000K (50)			
			D 160mm (16)			4480lm (448)				
			D 190mm (19)			6020lm (602)				
			D 225mm (22)			8540lm (854)				