
## Kernel Solar Street Light



Harness the power of the sun with this energy-efficient LED Solar Street Light. Designed to charge during the day and illuminate at night, it features an automatic on/off function for effortless operation. Easily adjust brightness and settings from a distance with the included remote control.







## **General Information**

Shape	Rectangular
Mounting	Surface Mounted
Lighting Application	Outdoor, Street, Road Side
Dimension	L 385mm   500mm W 132mm   210mm
Housing Material	Die-Cast Aluminum
Housing Color	Black
Ingress Protection	IP65

## Lamp Characteristics

Lатр Туре	LED
Light Source	SMD
Luminous Flux	20000lm   40000lm   60000lm   120000lm   200000lm
Efficacy	100 lm/W
Color Temperature	3000K   4000K   6500K
Color Rendering Index	>80 Ra
Beam Angle	Wide Beam Angle

## **Electrical Information**

 Total Power
 200W | 400W | 600W | 1200W | 2000W

 Voltage
 6V

 Control Gear
 Solar Powered

Product Code Not interselectable**									
Brand (BR-)	Product (PRO)	Mounting (MO)	Dimension (DM)**	Body Color (B)	IP Rating (IP)	Lumen (LUM)**	сст <b>(ст)</b>	Beam Angle <b>(BA)</b>	Control (C)
Zarelux (ZL-) Kernel Solar Surface Mounted Street Light (KSS) (SM)	Surface Mounted	L 385mm (38)	Black (B)	IP65 (65)	20000lm (200)	3000K (30)	Wide Beam Angle (WB)	On-Off (O)	
	(SM)	L 500mm <mark>(50)</mark>	·		40000lm (400)	4000K (40)			
		L 500mm <mark>(50)</mark>			60000lm (600)	6500K <mark>(65)</mark>			
	L 500mm <mark>(50)</mark>			120000lm (120)					
	L 500mm <mark>(50)</mark>			200000lm (200)					

All Rights Reserved ® Zarelux 2025